

Sunny Inspire



Flexible PV Solar Modules: Key Features & Benefits

- Aesthetically using clear surface back-contact cells
- Made with light weight polymer materials, suitable to install on a curved surface
- N-type solar cell has no LID naturally
- Lower hot spot temperature, higher safety
- Lower shadow-blocking loss
- Better weak illumination response

Electrical Specifications

Model Type	GW-120FXC
Peak Power (Pmax)	120W
Module Efficiency	18.67%
Maximum Power Voltage (Vmp)	18.7V
Maximum Power Current (Imp)	6.45A
Open Circuit Voltage (Voc)	21.8V
Short Circuit Current (Isc)	6.85A
Power Tolerance	0~4.99W
Maximum System Voltage	600V
Normal Operating Cell Temp.	46 °C (+/- 2)

Mechanical Specifications



Cell type	IBC
Number of cells	3 x 10, total 30 cells
Weight	4.8kg [10.58lbs]
Dimensions	1020 x 630 mm [40.16 x 24.80 in]
Thickness	3mm [0.12in] Including jbox: 18mm [0.71in]
Junction Box	IP 67 waterproof
Cables	4.00mm ² , 500mm
Connectors	MC4 compatible

Temperature Coefficients

Power	-0.290%/°C
Voltage	- 0.230%/°C
Current	+0.050%/°C

Warranties & Certifications

Warranties	2 years product warranty, 25 years limited power warranty of 80% of the minimum specified power rating
------------	--



Unit: mm

Note: All electrical parameters are rated at standard test conditions (irradiance of 1000W/m², AM 1.5G, cell temperature 77°F/25°C)

Caution: Read Safety and Installation Instruction before using this product.

2025 Sunny Inspire Limited. All right reserved. Specifications included in this datasheet are subject to change without notice.

Sunny Inspire Limited

www.sunnyinspire.com

Rm 1505, 15/F Star House, No. 3 Salisbury Rd, TST, KLN, Hong Kong | T: +852-2736 2080 | info@sunnyinspire.com